

Chain Cleaner

Revision: 17/09/2015

Page 1 from 1

Technical data

Basis	Solvent mixture
Consistency	Liquid
Density	Ca. 0,80 g/ml
Volatile Organic Compounds (VOC)	98 %
Application temperature	5 °C → 30 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Chain Cleaner is a professional cleaner and degreaser for removing all kinds of dirt such as oil, grease and wax from chain, cassette, rear and front derailleur.

Properties

- Cleans and degreases
- High degreasing power
- Solvent based
- Suitable for all surfaces, carbon, aluminum and titanium.

Applications

- Fast and thorough cleaning of chain, cassette, front and rear derailleur.
- Removes all kinds of dirt such as oil, grease, cleaning detergents and wax in a safe manner.

Packaging

Colour: blue

Packaging: 1 L

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Application method

Application method: Apply as required. Let it work and then wipe dry with a clean cloth. Always rub in the same direction. Test for adverse effects on the surface in advance. Repeat if necessary. Subsequently always lubricate the drive chain again with Soudal Wet or Dry Lub.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Remarks

- Remove Chain Cleaner of bicycle frame and wheels to prevent staining.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. She is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions beyond our control, no liability under this publication are accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.